

ES-32E11H/ES-32E12H/ES-32E13H

2MP HD 4in1 Camera



DWDR



AWB



6KV
Protection



Day&Night



IP67

Specifications

| Model | ES-32E11H | ES-32E12H | ES-32E13H |
|---------------------|---|-----------|-----------|
| Camera | | | |
| Image Sensor | 1/2.9" 2MP CMOS | | |
| Efective Pixels | 1920*1080 | | |
| Shutter Time | 1/25s~1/50,000s (PAL);1/30s~1/60,000s (NTSC) | | |
| Image System | PAL/NTSC | | |
| Video Frame System | 1080P@25fps (PAL); 1080P@30fps (NTSC) | | |
| IR Distance | 10 ~ 20m | | |
| Video Output | AHD/TVI/CVI/CVBS | | |
| Lens | 2.8mm | 3.6mm | 6mm |
| Lens Mount | M12 | | |
| Horizontal FOV | 114° | 78° | 51° |
| S/N Ratio | ≥41dB | | |
| Functions | | | |
| OSD | UTC support based on DVR | | |
| AGC | Support | | |
| White Balance | Auto/Manual | | |
| Day & Night | Auto/Manual | | |
| Video Setting | Contrast/Sharpness/Color Gain/Format/DWDR/DNR | | |
| Language | Multi-Language | | |
| General | | | |
| Casing | Aluminium alloy | | |
| Ingress Protection | IP67 | | |
| Working Environment | -30°C ~ 60°C /Humidity 10%~90°C RH | | |
| Power Supply | DC12V±10% 1.5A | | |
| Power Consumption | 3.2W MAX (IR cut off) | | |
| Dimensions | Φ102x93.2mm | | |
| Net Weight | 360g | | |

Features

- IR distance:10-20m
- DNR, DWDR
- Lightning Protection up to 6KV
- AHD/TVI/CVI/CVBS video output
- IP67 ingress protection
- Video Linkage with Access Control System (BioSecurity 3.0)

Dimensions

