

DL-32D26B/DL-32D28B

2MP HD 4 in 1 Camera



DWDR



AWB



6KV
Protection



Day&Night



IP67



IK10

Specifications

Model	DL-32D26B	DL-32D28B
Camera		
Image Sensor	1/2.7" 2MP CMOS	
Efective Pixels	1920*1080	
Shutter Time	1/25s~1/50,000s (PAL);1/30s~1/60,000s (NTSC)	
Image System	PAL/NTSC	
Video Frame System	1080P@25fps (PAL); 1080P@30fps (NTSC)	
IR Distance	20-30m (30-50m optional)	
Video Output	AHD/TVI/CVI/CVBS	
Lens	2.8-12mm Varifocal	2.8-12mm Motorized
Lens Mount	Ø14	
Horizontal FOV	30°-99°	
S/N Ratio	≥41dB	
Functions		
OSD	UTC support based on DVR	
AGC	Support	
White Balance	Auto/ Manual	
Day & Night	Auto/ Manual	
Video Setting	Contrast/Sharpness/Color Gain/ Format/DWDR/DNR	
Language	Multi-Language	
General		
Casing	Aluminium alloy	
Ingress Protection	IP67	
Working Environment	-30°C ~ 60°C /Humidity 10%~90°C RH	
Power Supply	DC12V±10% 1.5A	
Power Consumption	3.5W MAX (IR cut off)	
Dimensions	Ø133.1x104.0mm	
Net Weight	500g	

Features

- IR distance: 20-30m
- 3D DNR, DWDR
- Lightning Protection up to 6KV
- AHD/TVI/CVI/CVBS video output
- IP67 ingress protection
- IK10
- Video Linkage with Access Control System(BioSecurity 3.0)

Dimensions

