

ZKMD532/552

Fixed IR Dome IP camera



H.264



IR Day & Night Camera



Colour



Megapixel



Motion Detection

Features:

- Super video quality, HD up to 720P/960P
- Multiple H.264 streams
- Day & Night function
- Built-in IR illuminators
- Built-in POE (optional)

Technical Specifications	
Product Model	ZKMD532
Product Name	1.0 Megapixel CMOS IR Dome IP camera
Camera Performance	
Image Sensor	1/4" CMOS
Image Resolution	1280*720
Minimum Illumination	1 Lux(IR off), 0 Lux(IR on)
Day/Night Mode	Automatically IR-cut filter
Lens Type	3.6mm fixed lens
IR Distance	1pc array IR light, 60°projection angle, 5~8 meters valid
Video/Audio	
Video Compression	H.264 main profile level 3
Video Resolution	ZKMD532: (Main stream: 1280*720; Secondary stream: 640*352; Third stream: 320x176) ZKMD552: (Main stream: 1280x960; 1280x720; Secondary stream: 640x480; 640x352; Third stream: 320x240; 320x176;)
Image streaming	32Kbits/s ~ 6144Kbits/s settable
Video Frame Rate	PAL: 1-25 frame NTSC:1-30 frame
Image settings	Brightness, Saturation, Contrast, Sharpness, Exposure
Audio Input	1 Mic input (optional)
Network	
Security	Multi-level users access with password protection
Network Interface	10Base-t/100Base-TX Ethernet interface
Supported Protocol	TCP/IP, HTTP, TCP, UDP, ARP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP/RTCP/RTP, ONVIF, P2P
Alarm and Event Management	
Motion Detection	4 independent detection areas settable
Control Port	Reset
Alarm Trigger	Motion detection
Alarm Events	Alarm via email server(send snapshot);Upload photo to FTP server
General	
Casing	Camera: Metal(Aluminum Alloy) Color: White
Power Supply	12V DC ≥1A POE: 802.3af POE standard(optional)
Power Consumption	5W
Working Conditions	-10 ~ +50 °C, 10~95 %RH
Weight	N.W.: 0.5 KGS G.W.: 0.93KGS
Installation	Wall-mounted